

TERMOSALDATRICI
TRAY SEALERS
TERMOSELLADORAS
THERMOSCELLEUSES

TRE 25 PROFESSIONAL

SALDATURA

CARATTERISTICHE

Pannello comandi a tempo
1 modi di lavoro
9 programmi memorizzabili
stop ciclo di lavoro
Ciclo di lavoro automatico
Caricamento vaschette manuale

CHARACTERISTICS

Timed control panel
1 work modes
9 storable programs
Working cycle stop
Automatic work cycle
Manual tray loading

CARACTERÍSTICAS

Panel de control temporizado
1 modos de trabajo
9 programas memorizables
Posibilidad de parar al ciclo de trabajo
Ciclo de trabajo automático
Posicionamiento manual de las bandejas

CARACTÉRISTIQUES

Panneau de commande temporisé
1 modes de travail
9 programmes stockables
Arrêt le cycle de travail
Cycle de travail automatique
Chargement manuel des bacs



Optional su richiesta - Optional on request - Opcionales sobre pedido - En option sur demande

260x190 COD. A



STAMPO SINGOLO
Single mould
Molde 1 emprenta
outillage simple

230x190 COD. B



STAMPO SINGOLO
Single mould
Molde 1 emprenta
outillage simple

190x137 COD. C



STAMPO SINGOLO
Single mould
Molde 1 emprenta
outillage simple

180x180 COD. D



STAMPO SINGOLO
Single mould
Molde 1 emprenta
outillage simple

Modello Model Modelol Modèle	Dimensione macchina overall dimension dimensiones Taille de la machine	altezza max. Vaschetta max height of the tray altura máxbandeja hauteur max. Barquette	film di saldatura roll bobina bobine	Alimentazione voltage alimentación tension	Potenza power potencia pulsance	Peso weight peso poids	movimentazione
TRE 25 SA	263x500x542 mm	100 mm	220 mm Ø 200 mm	220 V-50-60 Hz	2800 W	40 kg	elettrica